

# WEDS ADVENTURE MUD VANCE 02

PRODUCED BY WEDS ADVENTURE



Experience the Difference..  
Experience Japan Quality.



[LAND CRUISER]  
SIZE : F/R : 20x9.5J INSET 55

SPECIAL THANKS ■ M'z SPEED

[LAND CRUISER PRADO]  
SIZE : F/R : 18x8.0J INSET 20



## MUD VANCE 02 JWL, JWL-T compliance

Code	Size	Inset	HOLE	P.C.D.	HUBφ	Price	JWL	JWL-T
37597	18×8.0J	20	6	139.7	106φ	¥45,000	●	●
37598	20×9.5J	55	5	150	110φ	¥65,000	●	●

■ DISK FINISH : BLACK POLISH ■ INCLUDES : Center Cap, Aluminum Air Valve  
 ■ NUT HOLE DIAMETER : 18inch=φ30 20inch=φ32  
 ■ APPLICATION : LEXUS LX, TOYOTA LAND CRUISER, TOYOTA LAND CRUISER PRADO,  
 TOYOTA FJ CRUISER, TOYOTA HILUX SURF

### REPAIR PARTS MUD VANCE 02

● Center Caps(#52758).....JPY 3,000  
 ● Alloy Valve(#527A2B).....JPY 1,500




20 × 9.5J  
INSET 55 / 5H-150

18 × 8.0J  
INSET 20 / 6H-139.7



### AMF process outline

Spinning Machine  
Roller Arm




#### ① Casting

Unlike other generic wheels, the AMF process does not simultaneously cast a wheel face and barrel. Instead, the disk face is low pressure cast with an unformed barrel which will be "stretched" into shape.

#### Aluminum casted with AMF

As the aluminum is stretched, the density of the grain structure rises and high material strength is achieved.



#### Standard casted aluminum

Since the aluminum is simply poured into a mold, the overall material density is poor, resulting in an end product with low strength.

#### ② Spinning

A dedicated spinning machine forms the wheel's barrel. The main body of the wheel is heated, as rollers work to extend the wheel.

#### ③ Finish

After the spinning process is complete, the wheel enters paint processing and finishing.